



Synesso Cyncra Specifications

Model	1 Group	1 Group	2 Group	3 Group
Voltage, Single Phase	110	220	220	220
Hertz	60	50 / 60	50 / 60	50 / 60
Amps - max draw	20	16	28	36
Brew & Steam Specifications:				
Watts per Element, Steam Tank	1000	1000 x 2	2000 x 2	2500 x 2
Total Steam Element Wattage	1000	2000	4000	5000
Steam Tank Capacity (Liters)	3.2	3.2	7.7	12.3
Watts per Element, Brew Tank	700	700	700 x 2	700 x 3
Brew Tank Capacities (Liters)	1.9	1.9	1.9 x 2	1.9 x 3
Machine Dimensions:				
	Inches / mm	Inches / mm	Inches / mm	Inches / mm
Height (Steam Wand 21", Handle 20.5")	18" / 457	18" / 457	18" / 457	18" / 457
Width (Steam Handle to Handle add 3")	18" / 457	18" / 457	29" / 736	40" / 1016
Depth	23" / 584	23" / 584	23" / 584	23" / 584
Weights & Dimensions:				
	Lbs / Kgs	Lbs / Kgs	Lbs / Kgs	Lbs / Kgs
Machine Weight, Empty	106 / 48	106 / 48	154 / 70	190 / 86
Machine Weight, Full of Water	115 / 52	115 / 52	173 / 77	215 / 98
Shipping Weight (approximate)	175 / 80	175 / 80	225 / 103	270 / 123
Boxed Dimensions: L" x W" x H"	20" x 30" x 31"	20" x 30" x 31"	41" x 32" x 31"	49" x 32" x 31"
Boxed Dimensions: L x W x H m/m	508x762x787	508x762x787	1042x762x787	1245x813x787
Plumbing (Compression)	3/8" OD	3/8" OD	3/8" OD	3/8" OD

- Certified by ETL for Sanitation to NSF / ANSI Standard 4
- Certified by ETL for Electrical Safety to ANSI / UL Standard 197
- Certified by ETL for Electrical Safety to CSA Standard C22.2 No. 109
- CE Compliant (By request)
- C-Tick Compliant (By request)

